Ratchet Action Lever Clamps The safe, fast, totally vibration-proof clamp

HARDENED PRESSURE PLATE

RAIL, FIXED JAW AND PRESSURE PLATE ... heat formed in one piece from cold drawn

profiled steel - tempered and galvanized

RATCHET MECHANISM ... fast, precise, totally vibration-proof clamping.

SURFACE HARDENED, STEEL CAM ... exceptional wear with minimum friction

POLY COATED

RELEASE TRIGGER

ISO 9001 CERTIFIED

It's All About the Quality.

DROP FORGED SLIDING ARM ... electro-galvanized, tempered steel

> POWDER COATED CLAMPING LEVER ... ergonomically shaped for comfort and leverage



This clamp is essential in those applications where vibration causes a conventional clamp to "walk" ... the lever clamp stays firmly in place even when you're using power tools such as a router or jig saw.

In addition, the ratchet design is the fastest clamping action available and is perfect for applications where there is a need to install and release a number of clamps in a minimum of time ... a quick release button releases clamping pressure instantly.

NOMINAL NOMINAL CATALOG THROAT NOMINAL CLAMPING NUMBER DEPTH OPENING PRESSURE LC-4 23/8" 4" 400 LBS. LC-6 31/8" 6" 500 LBS. LC-8 4" 8" 770 LBS. LC-10 43/4" 10" 880 LBS. LC-12 51/2" 12" 1110 LBS. LC-20 5" 20" 1440 LBS.				
LC-6 31/8" 6" 500 LBS. LC-8 4" 8" 770 LBS. LC-10 43/4" 10" 880 LBS. LC-12 51/2" 12" 1110 LBS.		THROAT		CLAMPING
LC-8 4" 8" 770 LBS. LC-10 4³/₄" 10" 880 LBS. LC-12 5¹/₂" 12" 1110 LBS.	LC-4	23/8"	4"	400 lbs.
LC-10 4 ³ / ₄ " 10" 880 LBS. LC-12 5 ¹ / ₂ " 12" 1110 LBS.	LC-6	31/8"	6"	500 lbs.
LC-12 5 ¹ / ₂ " 12" 1110 LBS.	LC-8	4"	8"	770 lbs.
	LC-10	43/4"	10"	880 LBS.
LC-20 5" 20" 1440 LBS.	LC-12	51/2"	12"	1110 LBS.
	LC-20	5"	20"	1440 lbs.

Jamacc[™] Pipe Clamp Fixtures

These clamps feature: plated spindles to prevent rust & corrosion;

Catalog Number	Pipe Diameter
PC-12	1/2"
PC-34	3/4"

"clutch" action grips bar automatically; large clamping surface - positive grip; large handle - positive pressure.

pipe not included

Jamacc™ Steel Spring Clamps

CATALOG NUMBER	Nominal Opening	Maximum Opening	Clamping Pressure
SC1-HT	1"	$1^{1/4}$ "	33.0 LBS.
SC2-HT	2"	21/4"	49.5 LBS.
SC3-HT	3"	$3^{5/_{16}}$ "	66.0 LBS.
SC4-HT	4"	5"	63.0 LBS.

These clamps feature: heavy duty springs for more pressure and longer life; nickel plating - won't rust or mark work piece; heavy duty vinyl tips and handles won't mar clamping surfaces.



