
WS Angle Clamps



Catalog Number	Different Material Thickness	Uniform Material Thickness	Clearance For T-Joints
WS-3	SIDE ONE: $^{7/\!\!/_8}$ " SIDE TWO: $2^{1/\!\!/_2}$ "	SIDE ONE: 2" SIDE TWO: 2"	1 ¹ /8"
WS-6	side one: 1" side one: 6"	SIDE ONE: 4" SIDE TWO: 4"	27/16"
TK-6 – Table Clamps (pair)			

The Convenient Portable Vise Clamp


This clamp is a must for every toolbox as a portable vise or work hold-down fixture.

Highly versatile, the S-10 and S-15 are ideal for holding rounds, rectangles and odd-shaped objects. Its lightweight, sturdy construction makes this a great tool for home, cottage, hobby or recreational use ... and is particularly suited to holding delicate mechanical parts or assemblies.

The Vise Clamp features: a galvanized spindle with large Acme thread; nonmarring, glue-resistant jaws; removable galvanized guide bars, which when removed allow jaws to swivel accommodating irregular shapes.



These versatile clamps are designed to always hold, fix and align material at a 90° angle and adjust automatically to variations in wood thickness. Their accuracy makes them ideal for many applications including cabinet work, furniture assembly, framing and their compact size fits easily into a tool box for site work.





The WS features: Galvanized spindle with large Acme thread; accurate, durable, die cast jaws are plastic-coated to protect work; open design allows ample clearance to screw, dowel or staple material together while gluing.

TK-6 table clamp ... holds clamp to work table - one pair included with the $S\mathchar`-10$ and S-15 Vise Clamps ... available as an accessory for WS Angle Clamps



GS-11 Miter Clamp ... for angled joints from 45° to 120° .

NOMINAL

OPENING

4"

6"

CATALOG

NUMBER

S-10

S-15

Swivel clamping jaws, fitted with nonmarking surfaces, will draw joint together as screw is tightened, regardless of the angle. Rigid steel base fitted with 3 large anti-slip pads. Clamp body is made of shock resistant super polyamid.

Catalog	Maximum	
Number	Opening	
GS-11	4"	

NOMINAL.

Width

3 5/8"

3 5/8"

